

HI - LIGHTER

External Lighting



Product Overview

LTC Hi-Lighter , with sleek design blend smoothly with it's environment and deliver optimum performance & sustainability

- Light output : Up to 21,600Lm
- IP66 Rating
- Thermal rating: 50 °C
- Surge protection
- Tiltable luminaire head
- Glare free optimized light distribution
- Multiple light distribution options
- Daylight sensor (optional)
- Smart Control system options
- Mounting Height: 8 m - 12 m



Product Applications

- Street lighting
- Area lighting
- Pedestrian walkways
- Parks
- Railway lighting
- Car parks
- Various public and commercial spaces
- And many more external lighting application.

- Standard warranty: 5 years *
- High grade Aluminium alloy housing: Gray finish
- Mounting spigot sizes (34 mm,42mm,60mm & 76mm)
- Peace of mind: Auto power cutoff when light fixture housing opened
- Ease of maintenance : No tools required to open luminaire housing or to replace LED driver
- Customizable to specific project requirements.





Main Features

Product Name:	Hi-Lighter
AC Inputc:	100-240 V AC , 50/60Hz
Input Surge Protection:	6kV line-line, 12kV line-earth
System Efficacy:	Up to 120 Lm/W
CRI Range:	CRI>70 (CRI 80 -Optional)
CCT Range:	3000K, 4000K or 5000K
Luminous flux:	3,600Lm (30W) 6,000Lm (50W) 8,400Lm (70W) 10,800Lm (90W) 14,400Lm (120W) 18,000Lm (150W) 21,600Lm (180W)
Power options:	30 W, 50W, 70W, 90W, 120W, 150W or 180W
Light distribution:	Type II Medium (8 types of optics available)
LED Lifetime:	>200,000Hrs (Ta=30°C@L70)
Operating Temperature Range:	- 30 °C to 50 °C
Lighting control systems:	Daylight sensor, 1-10V dimming, Timer control,DALI ,Centralized smart control etc.

Hi - Lighter Options

Modern aesthetically pleasing street light with numerous customizable features & smart control system.



Contact Us

LTC Head Office:

Sales: 1300 832 372

Email: sales@lighttc.com.au

Admin: 1300 832 372

Email: admin@lighttc.com.au

Website: www.lighttc.com.au



Address:

251 Rawson Street,
Auburn, NSW. 2144. Australia.